2022 **KLR®650 TRAVELER**









130/80-17

POWER

Scan with camera

to view videos,

key features

and more.

	I ONEN		Front Brakes	Single 300mm disc with 2-piston calipers,
	Engine	4-Stroke, single cylinder, DOHC		ABS
	Displacement	652cc	Rear Brakes	Single 240mm disc with single-piston caliper, ABS
	Bore x Stroke	100.0 x 83.0mm		
	Compression Ratio	9.8:1	DETAILS	
	Maximum Torque	39.1 lbft. @ 4,500rpm	Frame Type	Tubular, Semi-Double Cradle
			Rake/Trail	30.0°/4.8 in
	Fuel System	DFI w/40mm Throttle Body	Overall Length	89.8 in
	Ignition	CDI	Overall Width	38.2 in
	Transmission	5-speed, return shift with wet multi-disc manual clutch	Overall Height	57.7/56.3 in (screen hi/lo)
	Final Drive	Sealed Chain	Ground Clearance	8.3 in
	PERFORMANCE		Seat Height	34.3 in
			Curb Weight	471.7 lb*
	Eropt	41mm toloccopic fork/70 in		

Rear Tire

Front 41mm telescopic fork/ 7.9 in Suspension / Wheel Travel Uni-Trak[®], single shock with adjustable Rear rebound damping and adjustable spring Suspension / Wheel Travel preload / 8.0 in **Front Tire** 90/90-21

Specifications subject to change. Visit nicaragua.kawasaki-la.com for full product details.

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A.

Fuel Capacity

Color Choices

Wheelbase

Warranty

6.1 gal

60.6 in

12 Months

Pearl Lava Orange