JET SKI[®] STX[®] 160





CRYSTAL WHITE/VIBRANT BLUE



POWER

Engine	4-stroke, DOHC, four valves per cylinder, 4-cylinder inline	Lubrication	c r
Displacement	1,498cc	Coupling Oil Capacity	5
Bore x Stroke	83.0 x 69.2mm	Fuel Capacity	2
Compression Ratio	10.6:1	Load Capacity	L
Induction	Naturally aspirated	Storage Capacity	3
Maximum Boost	N/A	DETAILS	
Cooling System	Inducted water		
Fuel System	DFI® with 60mm throttle body	Overall Length Overall Width	1
Ignition	TCBI with Digital Advance	Overall Height	Z
Starting System	Electric	Curb Weight	ξ
Propulsion System	148mm jet pump, axial-flow, single stage	Seating Capacity	
Impeller	3-blade, oval-edge stainless steel	Color Choices	(
		Warranty	1

PERFORMANCE

Lubrication	Semi-dry sump system
Coupling	Direct drive from engine
Oil Capacity	5.3 qt
Fuel Capacity	20.6 gal
Load Capacity	496 lb
Storage Capacity	35.0 gal

Overall Length	124.1 in
Overall Width	46.5 in
Overall Height	45.4 in
Curb Weight	864.4 lb*
Seating Capacity	3
Color Choices	Crystal White/Vibrant Blue
Warranty	12 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Ride responsibly. Kawasaki believes safety begins with us and continues with you. Always wear a USCG-approved personal flotation device, eyewear, gloves, footwear, and a wet suit or clothing that provides equivalent protection (board shorts with neoprene liner). Never ride under the influence of drugs or alcohol. Respect the rights of shoreline residents and other marine recreationists. Boat smart from the start. Take a Boating Safety course; for more information visit www.USCGBoating.org. Jet Ski® watercraft are inboard powerboats and their use is subject to all applicable federal, state, and local boating laws. Read Owner's Manual and all on-product warnings. ©2024 Kawasaki Motors Corp., U.S.A.