## <sup>2020</sup> **KX<sup>™</sup>100**







Single 220mm petal disc with dual-piston

### POWER

Engine	2-stroke single with exhaust power valve, liquid-cooled	
Displacement	99cc	
Bore x Stroke	52.5 x 45.8mm	
Compression Ratio	10.2:1 (low speed) - 8.7:1 (high speed)	
Fuel System	28mm Keihin carburetor	
Ignition	CDI with digital advance	
Transmission	6-speed, return shift, with wet multi-disc manual clutch	
Final Drive	Chain	

# caliper Rear Brakes Single 220mm petal disc with single-piston caliper

90/100-16

#### DETAILS

**Rear Tire** 

**Front Brakes** 

a)			
	Frame Type	High-tensile steel perimeter design withsubframe member	
	Rake/Trail	29°/4.3 in	
i-disc	<b>Overall Length</b>	75.6 in	
	Overall Width	30.1 in	
	Overall Height	45.3 in	
	Ground Clearance	13.0 in	
e fork /10.8 in	Seat Height	34.3 in	
	Curb Weight	169.7 lb*	
	Fuel Capacity	1.32 gal	
lamping 3 in	Wheelbase	51.6 in	
	Color Choices	Lime Green	
	Warranty	Not Available	

### PERFORMANCE

Front Suspension / Wheel Travel	36mm inverted telescopic cartridge fork with 20-way compression damping/10.8 in
Rear Suspension / Wheel Travel	Uni-Trak® gas charged shock with piggyback reservoir with 24-way compression and 21-way rebound damping plus adjustable spring preload/10.8 in
Front Tire	70/100-19





1 🗉

\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit nicaragua.kawasaki-la.com for full product details.