

2020  
KX™ 450



POWER

Engine	4-stroke single, DOHC, liquid-cooled
Displacement	449cc
Bore x Stroke	96.0 x 62.1mm
Compression Ratio	12.5:1
Fuel System	DFI® with 44mm Keihin throttle body
Ignition	Digital CDI with electric start
Transmission	5-speed, return shift, with wet multi-disc manual clutch and hydraulic clutch actuation
Final Drive	Chain

PERFORMANCE

Front Suspension / Wheel Travel	49mm inverted telescopic coil-spring fork with 16-way compression damping and 16-way rebound damping/12.0 in
Rear Suspension / Wheel Travel	Uni-Trak® gas charged shock with piggyback reservoir with dual-range (4 turns stepless high speed/19-way low-speed) compression damping, 38-way rebound damping and adjustable preload/12.1 in

Front Tire	80/100-21
Rear Tire	120/80-19
Front Brakes	Single semi-floating 270mm Braking® petal disc with dual-piston caliper
Rear Brakes	Single 250mm Braking® petal disc with single-piston caliper

DETAILS

Frame Type	Aluminum perimeter
Rake/Trail	27.6° / 4.8 in
Overall Length	86.0 in
Overall Width	32.7 in
Overall Height	50.2 in
Ground Clearance	13.4 in
Seat Height	37.6 in
Curb Weight	232.3 lb without fuel / 242.4 lb*
Fuel Capacity	1.64 gal
Wheelbase	58.5 in
Color Choices	Lime Green
Warranty	Not Available

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [nicaragua.kawasaki-la.com](http://nicaragua.kawasaki-la.com) for full product details.