





_	_		_	_
D	n	W	E	D
Г		w	Г	П

Engine 2-stroke single with exhaust power valve, liquid-cooled

Displacement 64cc

Bore x Stroke 45.5 x 41.6mm

Compression Ratio 8.4:1

Fuel System 24mm Mikuni carburetor

Ignition CDI with digital advance

Transmission 6-speed, return shift, with wet multi-disc

manual clutch

Final Drive Chain

PERFORMANCE

Front Suspension / Wheel Travel 33mm leading axle telescopic fork with 4way rebound damping/8.3 in

Rear Suspension / Wheel Travel Uni-Trak® single shock system with 4-way rebound damping and fully adjustable spring preload/9.4 in

Front Tire 60/100-14

Rear Tire 80/100-12

Front Brakes Single 180mm disc with single-piston

caliper

Rear Brakes Single 180mm disc with single-piston

caliper

DETAILS

Frame Type Tubular, semi-double cradle

Rake/Trail 27°/2.4 in

Overall Length 62.6 in

Overall Width 29.9 in

Overall Height 37.6 in

Ground 12.0 in Clearance

Seat Height 29.9 in

Curb Weight 132.2 lb*

Fuel Capacity 1.0 gal

Wheelbase 44.1 in

Color Choices Lime Green

Warranty Not Available

Scan with camera to view videos, key features and more.

