







D	N	V	V	F	P
Г		v	v	Г	П

Engine 2-stroke single with exhaust power valve, liquid-cooled

Displacement 84cc

Bore x Stroke 48.5 x 45.8mm

Compression 10.9:1 (low speed) - 9.0:1 (high speed)

Ratio

Fuel System 28mm Keihin carburetor

Ignition Electric CDI with digital advance

Transmission 6-speed, return shift, with wet multi-disc

manual clutch

Final Drive Chain

Front Brakes	Single 220mm petal disc with dual-piston caliper
Rear Brakes	Single 220mm petal disc with single-piston caliper

90/100-14

DETAILS

Rear Tire

High-tensile steel perimeter design with **Frame Type** subframe member 29° /3.8 in Rake/Trail **Overall Length** 72.0 in **Overall Width** 30.1 in **Overall Height** 43.3 in 11.4 in Ground Clearance **Seat Height** 32.7 in **Curb Weight** 165.3 lb* **Fuel Capacity** 1.32 gal

49.8 in

Lime Green

Not Available

PERFORMANCE

Front
Suspension /
Wheel Travel

36mm inverted telescopic cartridge fork with 20-way compression damping/10.8 in

Rear Suspension / Wheel Travel Uni-Trak® single shock system with 24-way compression and 21-way rebound damping, plus adjustable spring preload/10.8 in

Front Tire

70/100-17





Wheelbase

Warranty

Color Choices