## JET SKI® STX®160X









## **POWER**

Engine 4-stroke, DOHC, four valves per cylinder, 4-

cylinder inline

Displacement 1,498cc

Bore x Stroke 83.0 x 69.2mm

Compression

Ratio

10.6:1

Induction Naturally aspirated

Maximum Boost N/A

**Cooling System** Inducted water

Fuel System DFI® with 60mm throttle body

**Ignition** TCBI with digital advance

**Starting System** Electric

Propulsion

Propulsion System

148mm jet pump, axial-flow, single stage

Impeller 3-blade, oval-edge stainless steel

Thrust 957 lb

## **PERFORMANCE**

**Lubrication** Semi-dry sump system

**Coupling** Direct drive from engine

Oil Capacity 5.3 qt.

Fuel Capacity 20.6 gal.

Load Capacity 496 lb.

Storage 35 gal. Capacity

## **DETAILS**

Overall Length 124.1 in.

Overall Width 46.5 in.

Overall Height 45.4 in.

Curb Weight 864.4 lb.\*

Seating Capacity

3

**Color Choices** Ebony/Riptide Turquoise

**Warranty** 12 Month Limited Warranty

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

KAWASAKI CARES: Ride responsibly. Kawasaki believes safety begins with us and continues with you. Always wear a USCG-approved personal flotation device, eyewear, gloves, footwear, and a wet suit or clothing that provides equivalent protection (board shorts with neoprene liner). Never ride under the influence of drugs or alcohol. Respect the rights of shoreline residents and other marine recreationists. Boat smart from the start. Take a Boating Safety course; for more information visit www.USCGBoating.org. Jet Ski® watercraft are inboard powerboats and their use is subject to all applicable federal, state, and local boating laws. Read Owner's Manual and all on-product warnings. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit nicaragua.kawasaki-la.com for full product details.