
MULE PRO-FX™









POWER

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

Maximum Torque 48.0 lb-ft @ 3500 rpm

Bore x Stroke 2.83x2.62 in

Compression Ratio

Fuel System DFI® with 34mm throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output

(max)

75 amp

CAPABILITY

Front Suspension / Double wishbone/8.7 in **Wheel Travel**

Rear Suspension / **Wheel Travel**

Double wishbone/8.5 (L) /8.7 (R) in

Front Tires 26x9.00-12, radial

26x11.00-12, radial

Steering

Rear Tires

Rack-and-pinion

Park Brake Type

Independent, Mechanical Disc

Front Brakes

Dual Disc, 2 piston caliper

Rear Brakes

Dual Disc, 1 piston caliper

Ground Clearance 10.4 in

Fuel Capacity 7.9 gal **Turning Radius** 16.0 ft

Cargo Bed 54.1 x 53.3 x 11.0 in

Dimensions (LxWxH)

Cargo Bed Load 1000 lb (600 lb for California models)

Capacity

Payload Capacity

1616 lb (1264 lb California model)

Seating Capacity 3

2000 lb **Towing Capacity**

Lighting (2) Halogen headlights, (2) Halogen tail/brake lights

DETAILS

Overall Length 133.3 in

Overall Width 64.0 in

Overall Height 77.4 in

Curb Weight 1816.9 lb*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer,

> fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT warning indicator, neutral, reverse and parking indicators, seatbelt

reminder lamps

Color Choices Super Black

Warranty Kawasaki 3-Year Limited Warranty



