MULE PRO-FXT™







	N	N	M	Œ	D
	U	ľ	ľ	E	Л

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

Maximum Torque 48.0 lb-ft @ 3500 rpm

Bore x Stroke 2.83x2.62 in

Compression Ratio 9.5:

Fuel System DFI® with 34mm throttle body

75 amp

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Ye

Alternator Output

(max)

10.2 in

Fuel Capacity

Ground Clearance

7.9 gal

Turning Radius

16.0 ft

Cargo Bed Dimensions 42.7 x 53.7 x 11.0 in (3-person)22.0 x 53.7 x 11.0 in (6-person)

(LxWxH)

Capacity

1000 lb (3-person)350 lb (6-person)(600 lb for

California models)

Payload Capacity

Cargo Bed Load

1616 lb (1264 lb California model)

Seating Capacity

3-person (1 row), 6 person (2 row)

Towing Capacity

2000 lb

Lighting

(2) Halogen headlights, (2) Halogen tail/brake lights

CAPABILITY

Front Suspension / Wheel Travel

Double wishbone/8.7 in

Rear Suspension / Wheel Travel Double wishbone/8.5 (L) /8.7 (R) in

Wheel Travel
Front Tires

26x9.00-12, radial

Rear Tires

26x11.00-12, radial

Steering

Rack-and-pinion

Park Brake Type

Independent, Mechanical Disc

Front Brakes

Dual Disc, 2 piston caliper

Rear Brakes

Dual Disc, 1 piston caliper

DETAILS

Overall Length

Overall Width

64.0 in

133.3 in

Overall Height

77.6 in

Curb Weight

1887.5 lb*

Wheelbase

92.3 in

Instruments

Multi-function display includes digital speedometer,

fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT warning indicator, neutral, reverse and parking indicators, seatbelt

reminder lamps

Color Choices

Super Black

Warranty

Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

