

2020

# MULE PRO-FXT™ EPS

**Kawasaki**  
Let the Good Times Roll®



 TIMBERLINE GREEN

 BRIGHT WHITE



## POWER

|                                |   |
|--------------------------------|---|
| <b>Engine</b>                  | 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas                                |
| <b>Displacement</b>            | 812cc   |
| <b>Maximum Torque</b>          | 48.0 lb·ft @ 3500 rpm   |
| <b>Bore x Stroke</b>           | 2.83x2.62 in  |
| <b>Compression Ratio</b>       | 9.5:1   |
| <b>Fuel System</b>             | DFI® with 34mm throttle body  |
| <b>Transmission</b>            | Continuously Variable Transmission (CVT) with (H,L,N,R)                       |
| <b>Final Drive</b>             | Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock |
| <b>Engine Braking</b>          | Yes   |
| <b>Alternator Output (max)</b> | 75 amp  |

|                                     |   |
|-------------------------------------|---|
| <b>Ground Clearance</b>             | 10.2 in   |
| <b>Fuel Capacity</b>                | 7.9 gal   |
| <b>Turning Radius</b>               | 16.0 ft   |
| <b>Cargo Bed Dimensions (LxWxH)</b> | 42.7 x 53.7 x 11.0 in (3-person) 22.0 x 53.7 x 11.0 in (6-person)   |
| <b>Cargo Bed Load Capacity</b>      | 1000 lb (3-person) 350 lb (6-person) (600 lb for California models) |
| <b>Payload Capacity</b>             | 1616 lb (1264 lb California model)                                  |
| <b>Seating Capacity</b>             | 3-person (1 row), 6 person (2 row)                                  |
| <b>Towing Capacity</b>              | 2000 lb   |
| <b>Lighting</b>                     | (2) Halogen headlights, (2) Halogen tail/brake lights               |

## CAPABILITY

|  |  |
|--|--|
| <b>Front Suspension / Wheel Travel</b> | Double wishbone/8.7 in                       |
| <b>Rear Suspension / Wheel Travel</b>  | Double wishbone/8.5 (L) / 8.7 (R) in         |
| <b>Front Tires</b>                     | 26x9.00-12, radial                           |
| <b>Rear Tires</b>                      | 26x11.00-12, radial                          |
| <b>Steering</b>                        | Electric Power Steering (EPS), Tilt steering |
| <b>Park Brake Type</b>                 | Independent, Mechanical Disc                 |
| <b>Front Brakes</b>                    | Dual Disc, 2 piston caliper                  |
| <b>Rear Brakes</b>                     | Dual Disc, 1 piston caliper                  |

|                       |  |
|-----------------------|--|
| <b>Overall Length</b> | 133.3 in   |
| <b>Overall Width</b>  | 64.0 in  |
| <b>Overall Height</b> | 77.6 in  |
| <b>Curb Weight</b>    | 1911.7 lb*   |
| <b>Wheelbase</b>      | 92.3 in  |
| <b>Instruments</b>    | Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps |
| <b>Color Choices</b>  | Timberline Green, Bright White   |
| <b>Warranty</b>       | Kawasaki 3-Year Limited Warranty   |

Scan with camera  
to view videos,  
key features  
and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2020 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [nicaragua.kawasaki-la.com](http://nicaragua.kawasaki-la.com) for full product details.