
MULE PRO-FXT™ EPS CAMO









POWER

4-stroke, 3-cylinder, DOHC, liquid-cooled, gas **Engine**

Displacement 812cc

Maximum Torque 48.0 lb-ft @ 3500 rpm

Bore x Stroke 2.83x2.62 in

Compression Ratio 9.5:1

Fuel System DFI® with 34mm throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output 75 amp

(max)

Ground Clearance 10.2 in

7.9 gal **Fuel Capacity**

Turning Radius 16.0 ft

Cargo Bed

Dimensions (LxWxH)

person)

Cargo Bed Load

Capacity

1000 lb (3-person)350 lb (6-person)(600 lb for California models)

42.7 x 53.7 x 11.0 in (3-person)22.0 x 53.7 x 11.0 in (6-

Payload Capacity

1616 lb (1264 lb California model)

Seating Capacity

3-person (1 row), 6 person (2 row)

Towing Capacity

2000 lb

Lighting

(2) Halogen headlights, (2) Auxiliary LED headlights, (2)

Halogen tail/brake lights

CAPABILITY

Front Suspension / **Wheel Travel**

Double wishbone/8.7 in

Rear Suspension / **Wheel Travel**

Double wishbone/8.5 (L) /8.7 (R) in

Front Tires 26x9.00-12, radial **Rear Tires** 26x11.00-12, radial

Electric Power Steering (EPS), Tilt steering Steering

Park Brake Type Independent, Mechanical Disc **Front Brakes** Dual Disc, 2 piston caliper

Rear Brakes Dual Disc, 1 piston caliper

DETAILS

Overall Length 133.3 in

Overall Width 64.0 in

Overall Height 77.6 in

Curb Weight 1916.1 lb*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer,

> fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt

reminder lamps

Color Choices Realtree Xtra® Green Camo

Kawasaki 3-Year Limited Warranty Warrantv

Scan with camera to view videos, key features and more.

