MULE PRO-MX™ EPS CAMO







P	N	W	F	R

Engine 4-stroke, single cylinder, SOHC, 4-valve liquid-cooled

Displacement 695cc

Maximum Torque 42.7 lb-ft @ 5000 rpm

Bore x Stroke 4.02x3.35 in

Compression Ratio 10.3:1

Fuel System DFI® with 44mm throttle body

Transmission Continuously Variable Transmission (CVT) with

centrifugal clutch, (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output 35.7 amp

(max)

Rear Brakes Dual Disc, 1 piston caliper

Ground Clearance 10.6 in

Fuel Capacity 9.5 gal

Turning Radius 14.0 ft

33.4 x 44.1 x 9.1 in Cargo Bed **Dimensions (LxWxH)**

Cargo Bed Load

Capacity

Payload Capacity 1200 lb

Seating Capacity

Towing Capacity 1500 lb

Lighting (2) Halogen headlights, (2) LED headlights

700 lb (600 lb California models)

CAPABILITY

Front Suspension / Double wishbone/8.6 in **Wheel Travel**

Rear Suspension / Double wishbone/9.1 in **Wheel Travel**

Front Tires 25x10.00-12, radial

25x10.00-12, radial Electric Power Steering (EPS), Tilt steering **Steering**

Park Brake Type Independent, Mechanical Disc **Front Brakes** Dual Disc, 2 piston caliper

DETAILS

Overall Length 110.0 in

Overall Width 60.0 in

Overall Height 75.8 in

Curb Weight 1598.6 lb*

Wheelbase 78.9 in

Instruments Multi-function display includes digital speedometer,

> fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt

reminder lamps

Color Choices Camouflage TrueTimber® HTC Green

Kawasaki 3-Year Limited Warranty Warranty

Scan with camera to view videos, key features and more.

Rear Tires

