MULE SX[™] 4x4 FI









POWER

Engine 4-stroke, single-cylinder, OHV, air-cooled

Displacement 401cc

Maximum Torque 21.4 lb-ft @ 2400 rpm

Bore x Stroke 3.23x2.99 in

Compression Ratio

Fuel System Fuel injection

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output

(max)

22.9 amp

Rear Brakes	Drum
Ground Clearance	6.7 in
Fuel Capacity	4.2 gal

Turning Radius 10.8 ft

Cargo Bed Dimensions (LxWxH)

35.6 x 40.9 x 9.6 in

Cargo Bed Load Capacity

400 lb

Payload Capacity 915 lb **Seating Capacity**

Towing Capacity 1100 lb*

(2) Halogen headlights, (2) Halogen tail/brake lights

CAPABILITY

Front Suspension / MacPherson Strut/3.1 in **Wheel Travel**

Rear Suspension / Wheel Travel

Unit Swingarm/3.1 in

Front Tires

24x9.00-10

Rear Tires 24x11.00-10

Steering

Park Brake Type

Rack-and-pinion, Tilt steering

Independent, Mechanical Drum

Front Brakes Drum

DETAILS

Lighting

Warranty

Overall Length 106.7 in **Overall Width** 52.6 in **Overall Height** 70.9 in 1031.9 lb**

Curb Weight

Wheelbase 70.1 in

Instruments Fuel gauge, hour meter, oil temp light, parking brake

Color Choices Timberline Green, Dark Royal Red

Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

