NINJA® ZX™-6R ABS







CANDY STEEL FURNACE ORANGE/METALLIC FLAT SPARK BLACK



METALLIC SPARK BLACK/METALLIC FLAT SPARK BLACK



D	n	W	ľ	D
	U	W	IC	π

Engine 4-stroke, 4-cylinder, DOHC, 16-valve, liquid-

cooled

Displacement 636cc

Bore x Stroke 67.0 x 45.1mm

Compression

Ratio

12.9:1

Fuel System DFI® with 38mm Keihin throttle bodies (4) and

oval sub-throttles

Ignition TCBI with digital advance

Transmission 6-speed, return shift

Final Drive Sealed chain

Electronic Rider

Aids

Kawasaki Traction Control (KTRC), Power Mode, Kawasaki Intelligent anti-lock Brake System

(KIBS), Kawasaki Quick Shifter (KQS) (upshift

only)

PERFORMANCE

Front Suspension / Wheel Travel

41mm inverted Showa SFF-BP fork with top-out springs, stepless compression and rebound damping, adjustable spring preload/4.7 in

Rear Suspension / Wheel Travel

Bottom-link Uni-Trak® with gas-charged shock, stepless compression damping adjustment, 25-way adjustable rebound damping, fully adjustable spring preload/5.9 in

Front Tire 120/70 ZR17

Rear Tire 180/55 ZR17

Front Brakes Dual 310mm petal discs with dual radial-

mounted Nissin 4-piston monobloc calipers and

KIBS ABS

Rear Brakes Single 220mm petal discs with single-piston

caliper and KIBS ABS

DETAILS

Frame Type Tubular, diamond frame

Rake/Trail 23.5°/4.0 in

Overall Length 79.7 in

Overall Width 28.0 in

Overall Height 43.3 in

Ground 5.1 in

Clearance

Seat Height 32.7 in

Curb Weight 430.0 lb*

Fuel Capacity 4.5 gal

Wheelbase 55.1 in

Special Features N/A

Color Choices Candy

Candy Steel Furnace Orange/Metallic Flat Spark Black, Metallic Spark Black/Metallic Flat Spark

Black

Warranty 12 Month Limited Warranty



