

2020

NINJA® ZX™-6R ABS KRT EDITION

Kawasaki

Let the Good Times Roll®

 LIME GREEN/EBONY

POWER		Front Tire	120/70 ZR17
Engine	4-stroke, 4-cylinder, DOHC, 16-valve, liquid-cooled	Rear Tire	180/55 ZR17
Displacement	636cc	Front Brakes	Dual 310mm petal discs with dual radial-mounted Nissin 4-piston monobloc calipers and KIBS ABS
Bore x Stroke	67.0 x 45.1mm	Rear Brakes	Single 220mm petal discs with single-piston caliper and KIBS ABS
Compression Ratio	12.9:1	DETAILS	
Fuel System	DFI® with 38mm Keihin throttle bodies (4) and oval sub-throttles	Frame Type	Tubular, diamond frame
Ignition	TCBI with digital advance	Rake/Trail	23.5° / 4.0 in
Transmission	6-speed, return shift	Overall Length	79.7 in
Final Drive	Sealed chain	Overall Width	28.0 in
Electronic Rider Aids	Kawasaki Traction Control (KTRC), Power Mode, Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Quick Shifter (KQS) (upshift only)	Overall Height	43.3 in
PERFORMANCE		Ground Clearance	5.1 in
Front Suspension / Wheel Travel	41mm inverted Showa SFF-BP fork with top-out springs, stepless compression and rebound damping, adjustable spring preload/4.7 in	Seat Height	32.7 in
Rear Suspension / Wheel Travel	Bottom-link Uni-Trak® with gas-charged shock, stepless compression damping adjustment, 25-way adjustable rebound damping, fully adjustable spring preload/5.9 in	Curb Weight	430.0 lb*
		Fuel Capacity	4.5 gal
		Wheelbase	55.1 in
		Special Features	N/A
		Color Choices	Lime Green/Ebony
		Warranty	12 Month Limited Warranty



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit nicaragua.kawasaki-la.com for full product details.