
VULCAN® 900 CLASSIC LT









Single 300mm hydraulic disc

Single 270mm hydraulic disc

Semi-double cradle, high-tensile steel

130/90x16

180/70x15

25/4.3 in

97.0 in

39.6 in

58.3 in

5.3 in

POWFR

Engine 4-stroke, 55° V-twin, 4 valves per cylinder,

SOHC, liquid-cooled

Displacement 903cc/55.1 cu in

Bore x Stroke 88.0 x 74.2mm

Compression

Ratio

9.5:1

Maximum **Torque**

58.2 lb-ft @ 3500 rpm

Fuel System

DFI® 34mm throttle bodies (2) with sub-

throttle valves

Ignition

TCBI with digital advance

Transmission

5-speed with positive neutral finder

Final Drive

Kevlar-reinforced belt

PERFORMANCE

Front Suspension / **Wheel Travel** 41mm hydraulic telescopic fork/5.9 in

Rear Suspension / **Wheel Travel** Uni-Trak® swingarm, 7-way adjustable spring preload/4.1 in

Color Choices

Front Tire

Rear Tire

Front Brakes

Rear Brakes

DETAILS

Frame Type

Rake/Trail

Overall Length

Overall Width

Overall Height

Ground

Clearance

Seat Height

Curb Weight

Fuel Capacity

Wheelbase

Warranty

26.8 in 657.1 lb*

5.3 gal

64.8 in

Metallic Phantom Silver/ Metallic Carbon

Gray

24 Month Limited Warranty

Scan with camera to view videos. key features and more.

