VULCAN® 900 CUSTOM









POWER

Engine 4-stroke, 55° V-twin, 4 valves per cylinder,

SOHC, liquid-cooled

Displacement 903cc/55.10 cu in

Bore x Stroke 88.0 x 74.2mm

Compression

Ratio

9.5:1

Maximum Torque 58.2 lb-ft @ 3500 rpm

Fuel System DFI® 34mm throttle bodies (2), with sub-

throttle valves

Ignition TCBI with digital advance

Transmission 5-speed with positive neutral finder

Final Drive Kevlar-reinforced belt

PERFORMANCE

Front
Suspension /
Wheel Travel

41mm hydraulic telescopic fork/5.9 in

Rear Uni-Trak® swingarm, 7-way adjustable spring preload/4.1 in Wheel Travel

Front Tire 80/90x21

Rear Tire 180/70x15

Front Brakes Single 300mm hydraulic disc

Rear Brakes Single 270mm hydraulic disc

DETAILS

Frame Type Double cradle, high-tensile steel

Overall Length 94.7 in

Overall Width 35.2 in

Overall Height 44.1 in

Ground 5.5 in Clearance

Seat Height 27.0 in

Curb Weight 610.8 lb*

Fuel Capacity 5.3 gal

Wheelbase 64.8 in

Color Choices Metallic Matte Graphite Gray/Metallic Flat

Spark Black

Warranty 12 Month Limited Warranty



