2020 **Z400 ABS**





METALLIC MATTE GRAPHITE GRAY/METALLIC SPARK BLACK

CANDY STEEL FURNACE ORANGE/METALLIC FLAT SPARK BLACK



POWER

Engine	4-stroke, 2-cylinder, DOHC, liquid-cooled	
Displacement	399сс	
Bore x Stroke	70.0 x 51.8mm	
Compression Ratio	11.5:1	
Maximum Torque	28.0 lb-ft @ 8,000 rpm	
Fuel System	DFI® with 32mm throttle bodies	
Ignition	TCBI with digital advance	
Transmission	6-speed, return shift	
Final Drive	Sealed chain	

Rear Tire 150/60-17M/C 66H Single disc **Front Brakes Rear Brakes** Single disc

DETAILS

Compression Ratio	11.5:1	Frame Type	Trellis, high-tensile steel
Maximum	28.0 lb-ft @ 8,000 rpm	Rake/Trail	24.5°/3.6 in
Torque		Overall Length	78.3 in
Fuel System	DFI® with 32mm throttle bodies	Overall Width	31.5 in
Ignition	TCBI with digital advance	Overall Height	41.5 in
Transmission	6-speed, return shift	Ground	5.7 in
Final Drive	Sealed chain	Clearance	
		Seat Height	30.9 in
PERFORMANCE		Curb Weight	363.8 lb*
Front	Telescopic fork/4.7 in	Fuel Capacity	3.7 gal
Suspension / Wheel Travel		Wheelbase	53.9 in
Rear Suspension / Wheel Travel	Uni-Trak® swingarm/5.1 in	Color Choices	Metallic Matte Graphite Gray/Metallic Spark Black, Candy Steel Furnace Orange/ Metallic Flat Spark Black
Front Tire	110/70-17M/C 54H	Warranty	12 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit nicaragua.kawasaki-la.com for full product details.