VULCAN® 1700 VOYAGER® ABS







POWER		
Engine	4-stroke, 52-degree V-twin, liquid-cooled	
Displacement	1,700cc/103.7 cu in	
Bore x Stroke	102.0 x 104.0mm	
Compression Ratio	9.5:1	
Maximum	107.6 lb-ft @ 2750 rpm	

Maximum Torque	107.6 lb-ft @ 2750 rpm
Fuel System	DFI 42mm Throttle Bodies (2)
Ignition	TCBI w/ Electronic Advance
Transmission	6-speed with overdrive and positive neutral finder
Final Drive	Carbon fiber-reinforced belt

Electronic Rider	Electronic cruise control, Kawasaki Advanced
Aids	Coactive-Braking Technology (K-ACT II) ABS

PERFORMANCE

Suspension / Wheel Travel	,
Rear Suspension / Wheel Travel	Swingarm with twin air-assisted shocks, with 4-way rebound damping/3.1 in

45mm Showa telescopic fork/5.5 in

Front Tire	130/90-16
Rear Tire	170/70-16
Front Brakes	Dual 300mm discs, dual four-piston calipers, K-ACT II ABS
Rear Brakes	Single 300mm disc, twin-piston caliper, K-ACT II ABS

DETAILS

Frame Type	Steel, double-cradle with box-section single-tube backbone
Overall Length	100.8 in
Overall Width	39.2 in
Overall Height	61.0 in
Ground Clearance	5.3 in
Seat Height	28.7 in
Curb Weight	895.2 lb*
Fuel Capacity	5.3 gal
Wheelbase	65.6 in
Special Features	Integrated audio system with SiriusXM ® and intercom headset compatibility
Color Choices	PEARL METEOR GRAY / METALLIC SPARK BLACK
Warranty	36 Month Limited Warranty



Front

