VULCAN® 900 CUSTOM









POWFR

Engine 4-stroke, 55-degree V-twin, liquid-cooled

Displacement 903cc/55.10 cu in

Bore x Stroke 88.0 x 74.2mm

Compression

Ratio

9.5:1

Maximum **Torque**

58.2 lb-ft @ 3500 rpm

Fuel System

DFI 34mm Throttle Bodies (2), with sub-

throttle valves

Ignition

TCBI w/ Electronic Advance

Transmission

5-speed with positive neutral finder

Final Drive

Kevlar-reinforced belt

PERFORMANCE

Front Suspension / **Wheel Travel** 41mm Showa telescopic fork/5.9 in

Rear Suspension / **Wheel Travel** Uni-Trak® swingarm, 7-way adjustable

spring preload/4.1 in

Front Tire 130/90-21

Rear Tire 180/70-15

Front Brakes Single 300mm hydraulic disc

Rear Brakes Single 270mm hydraulic disc

DETAILS

Semi-double cradle, high-tensile steel **Frame Type**

Rake/Trail 33° / 7.2 in

Overall Length 94.7 in

Overall Width 35.2 in

Overall Height 44.1 in

Ground 5.5 in Clearance

Seat Height 27.0 in

Curb Weight 610.8 lb*

Fuel Capacity 5.3 gal

Wheelbase 64.8 in

Color Choices CANDY STEEL FURNACE ORANGE / METALLIC

SPARK BLACK

12 Month Limited Warranty Warranty



