Kawasaki Let the Good Times Roll®





P	N	V	V	F	R
	u			_	

Engine 4-stroke, 4-cylinder, DOHC, 16-valve, liquid-

cooled

Displacement 948cc

Bore x Stroke 73.4 x 56.0mm

Compression

Ratio

10.8:1

Maximum 72.3 lb-ft @ 6,500 rpm

Torque

Fuel System

DFI® with Keihin 36mm throttle bodies

Ignition TCBI with electronic advance

Transmission 6-speed, return shift

Final Drive Sealed chain

Electronic Rider K

Aids

Kawasaki Traction Control (KTRC)

PERFORMANCE

Front
Suspension /
Wheel Travel

Inverted 41mm telescopic fork with (13-way) adjustable compression and (11-way) adjustable rebound damping, (15-turn) adjustable spring preload / 4.7 in

Rear Suspension / Wheel Travel

Horizontal back-link swingarm with adjustable rebound damping and spring preload / 5.5 in

Front Tire

Rear Tire 180/55 ZR17

Front Brakes

Dual 300mm disc, ABS

120/70 ZR17

Rear Brakes

Single 250mm disc, ABS

DETAILS

Frame Type Trellis, high tensile steel

Rake/Trail 25.0°/3.9 in

Overall Length 83.1 in

Overall Width 34.1 in

Overall Height 46.5 in

Ground Clearance

Seat Height 32.9 in

Curb Weight 474.1 lb (50-State Model)*

5.1 in

Fuel Capacity 4.5 gal

Wheelbase 57.9 in

Color Choices Candytone Green

Warranty 12 Month Limited Warranty



