

2021

# BRUTE FORCE® 750 4x4i

**Kawasaki**  
Let the Good Times Roll®



FIRECRACKER RED



## POWER

|                   |   |
|-------------------|---|
| Engine            | 4-stroke, V-twin, SOHC, liquid-cooled                                   |
| Displacement      | 749cc   |
| Bore x Stroke     | 85.0 x 66.0mm   |
| Compression Ratio | 9.3:1   |
| Fuel System       | DFI® with two 36mm throttle bodies                                      |
| Ignition          | Digital DC-CDI  |
| Transmission      | Automatic CVT (H,L,N,R)   |
| Final Drive       | Selectable 2WD/4WD with variable control front differential lock, shaft |

|                                 |   |
|---------------------------------|---|
| Electronic Power Steering (EPS) | No  |
| Turning Radius                  | 10.5 ft                                     |
| Towing Capacity                 | 1250 lb                                     |
| Total Rack Capacity             | 242.0 lb                                    |
| Rack Capacity, Front/Rear       | 88.0/176.0 lb                               |
| Lighting                        | 35W headlights, 5W taillight, 21W stoplight |

## CAPABILITY

|                                 |  |
|---------------------------------|--|
| Front Suspension / Wheel Travel | Double wishbone/6.7 in                                     |
| Rear Suspension / Wheel Travel  | Double wishbone/7.5 in                                     |
| Front Tires                     | AT 25 x 8-12   |
| Rear Tires                      | AT 25 x 10-12  |
| Front Brakes                    | Dual hydraulic 176mm discs with 2-piston calipers          |
| Rear Brakes                     | Sealed, oil-bathed, multi-disc with independent park brake |
| Ground Clearance                | 9.4 in   |
| Starting System                 | Electric   |
| Fuel Capacity                   | 5.0 gal  |

## DETAILS

|                  |  |
|------------------|--|
| Frame Type       | Double-cradle, high-tensile tubular steel  |
| Track Front/Rear | 36.4/35.0 in   |
| Overall Length   | 86.4 in  |
| Overall Width    | 46.5 in  |
| Overall Height   | 48.0 in  |
| Seat Height      | 35.8 in  |
| Curb Weight      | 688.0 lb*  |
| Wheelbase        | 50.6 in  |
| Instruments      | Speedometer, odometer, dual trip meters, fuel gauge, engine temp, clock, hour meter and 2WD/4WD icon, plus indicators for neutral, reverse, belt, and oil pressure |
| Color Choices    | Firecracker Red  |
| Warranty         | 12 Month Limited Warranty  |

Scan with camera  
to view videos,  
key features  
and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki ATVs with engines over 90cc are recommended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1-800-887-2887, or go to [www.atvsafety.org](http://www.atvsafety.org). ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [nicaragua.kawasaki-la.com](http://nicaragua.kawasaki-la.com) for full product details.