

2021

CONCOURS®14 ABS

Kawasaki
Let the Good Times Roll®



 METALLIC SPARK BLACK



POWER

Engine	4-stroke, 4-cylinder, DOHC, 4-valve, liquid-cooled
Displacement	1,352cc
Bore x Stroke	84.0 x 61.0mm
Compression Ratio	10.7:1
Maximum Torque	100.5 lb-ft
Fuel System	DFI® with 40mm throttle bodies (4)
Ignition	TCBI with electronic advance
Transmission	6-speed
Final Drive	Tetra-Lever shaft drive
Electronic Rider Aids	Kawasaki Advanced Coactive-Braking Technology (K-ACT) ABS System, Kawasaki Traction Control (KTRC)

Front Tire	120/70 ZR-17
Rear Tire	190/50 ZR-17
Front Brakes	Dual floating 310mm petal-style discs with four-piston calipers, ABS
Rear Brakes	Single 270mm petal-style disc, single-piston caliper, ABS

DETAILS

Frame Type	Monocoque Aluminum
Rake/Trail	26.0/4.4 in
Overall Length	87.8 in
Overall Width	31.1/39.4 wo/w saddlebags
Overall Height	52.9 in/57.7 in (windshield down/up)
Ground Clearance	4.9 in
Seat Height	32.1 in
Curb Weight	690.2 lb (672.5 w/o saddlebags)*
Fuel Capacity	5.8 gal
Wheelbase	59.8 in
Special Features	Electrically adjusted windshield
Color Choices	Metallic Spark Black
Warranty	36 Month Limited Warranty

PERFORMANCE

Front Suspension / Wheel Travel	43mm inverted, telescopic fork with adjustable rebound damping and spring preload/4.4 in
Rear Suspension / Wheel Travel	Tetra-Lever with stepless rebound damping adjustment and remote spring preload adjuster/5.4 in

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit nicaragua.kawasaki-la.com for full product details.