

2021

JET SKI® ULTRA® 310X

Kawasaki
Let the Good Times Roll®



EBONY/AMARILLO PEARL NEON



POWER		Thrust	1890 lb
Engine	Supercharged and intercooled, 4-stroke, DOHC, four valves per cylinder, inline 4-cylinder	PERFORMANCE	
Displacement	1,498cc	Lubrication	Semi-dry sump system
Bore x Stroke	83.0 x 69.2mm	Coupling	Direct drive from engine
Compression Ratio	8.2:1	Oil Capacity	5.3 qt.
Induction	Eaton Twin Vortices Series Roots-type supercharger with air-to-water intercooler	Fuel Capacity	20.6 gal.
Maximum Boost	16.8 psi	Load Capacity	496 lb.
Cooling System	Inducted water	Storage Capacity	56 gal.
Fuel System	DFI® with 60mm throttle body	DETAILS	
Ignition	TCBI with digital advance	Overall Length	132.7 in.
Starting System	Electric	Overall Width	47.0 in.
Propulsion System	160mm jet pump, axial-flow, single stage	Overall Height	45.3 in.
Impeller	3-blade, oval-edge stainless steel	Curb Weight	1051.8 lb.*
		Seating Capacity	3
		Color Choices	Ebony/Pearl Neon Yellow
		Warranty	12 Month Limited Warranty

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
KAWASAKI CARES: Ride responsibly. Kawasaki believes safety begins with us and continues with you. Always wear a USCG-approved personal flotation device, eyewear, gloves, footwear, and a wet suit or clothing that provides equivalent protection (board shorts with neoprene liner). Never ride under the influence of drugs or alcohol. Respect the rights of shoreline residents and other marine recreationists. Boat smart from the start. Take a Boating Safety course; for more information visit www.USCGBoating.org. Jet Ski® watercraft are inboard powerboats and their use is subject to all applicable federal, state, and local boating laws. Read Owner's Manual and all on-product warnings. ©2025 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit nicaragua.kawasaki-la.com for full product details.