KLX[®]230 ABS







4.10 x 18

P	N	V	M	F	R
	u	ľ	V	E	П

Engine 4-stroke single, SOHC, air-cooled

Displacement 233cc

Bore x Stroke 67.0 x 66.0mm

Compression

Ratio

9.4:1

DFI® with 32mm Keihin throttle body **Fuel System**

Ignition TCBI Electronic Advance

Transmission 6-speed, return shift with wet multi-disc

manual clutch

Final Drive Chain

DETAILS

Rear Tire

Front Brakes

Rear Brakes

High-tensile steel, box-section perimeter **Frame Type**

Single 265mm petal disc with a dualpiston caliper with Dual Purpose ABS

Single 220mm petal disc with single-

piston caliper with Dual Purpose ABS

Rake/Trail 27.5° / 4.6 in

82.9 in. **Overall Length**

Overall Width 32.9 in.

Overall Height 45.9 in.

Clearance

Ground

Seat Height 34.8 in.

Curb Weight 293.3 lb. / 295.5 lb. CA model*

10.4 in.

Fuel Capacity 2.0 gal.

Wheelbase 54.3 in.

Color Choices Lime Green

12 Months Warranty

PERFORMANCE

Front 37mm telescopic fork/8.7 in Suspension / **Wheel Travel** Uni-Trak® linkage system and single shock Rear with adjustable spring preload/8.8 in Suspension / **Wheel Travel Front Tire**





2.75 x 21