## KLX®300SM









130/70-17

piston caliper

piston caliper

## **POWER**

Engine 4-stroke single, DOHC, liquid-cooled

**Displacement** 292cc

Bore x Stroke 78.0 x 61.2mm

Compression

Ratio

11.1:1

Fuel System DFI® with 34mm Keihin throttle body

Ignition CDI

**Transmission** 6-speed, return shift with wet multi-disc

manual clutch

Final Drive Chain

## DETAILS

**Rear Tire** 

**Front Brakes** 

**Rear Brakes** 

Frame Type High-tensile steel, box-section perimeter

Single 300mm petal disc with a dual-

Single 240mm petal disc with single-

Rake/Trail 25.0°/2.8 in

Overall Length 86.4 in

Overall Width 31.1 in

Overall Height 45.1 in

**Ground Clearance** 

9.3 in

Seat Height 33.9 in

Curb Weight 304.3 lb\*

Fuel Capacity 2.0 gal

Wheelbase 56.5 in

Color Choices Lime Green/Ebony, Oriental Blue/Ebony

Warranty 12 Months

## **PERFORMANCE**

Front
Suspension /
Wheel Travel

43mm inverted cartridge fork with adjustable compression damping / 9.1 in

Rear Suspension / Wheel Travel Uni-Trak® gas charged shock with piggyback reservoir with adjustable rebound damping and spring preload/ 8.1

ın

Front Tire 110/70-17



