





D	N	W	Г	D
Г	U	W	E	Λ

Engine 4-stroke single, DOHC, liquid-cooled

Displacement 449cc

Bore x Stroke 96.0 x 62.1mm

Compression

Transmission

Ratio

12.5:1

Fuel System DFI® with 44mm Keihin throttle body

Ignition Digital CDI with 3 Coupler Options

5-speed, return shift, with wet multi-disc manual clutch and hydraulic clutch actuation

Final Drive Chain

PERFORMANCE

Front Suspension / Wheel Travel 49mm inverted telescopic coil-spring fork with 16-way compression damping and 16-way rebound damping/12.0 in

Rear Suspension / Wheel Travel Uni-Trak® gas charged shock with piggyback reservoir with dual-range (4 turns stepless high speed/19-way low-speed) compression damping, 22-way rebound damping and adjustable preload/12.1 in

Front Tire 80/100-21

Rear Tire 120/80-18

Front Brakes Single semi-floating 270mm Braking® petal

disc with dual-piston caliper

Rear Brakes Single 240mm Braking® petal disc with

single-piston caliper

DETAILS

Frame Type Aluminum perimeter

Rake/Trail 27.6°/4.7 in

Overall Length 86.0 in

Overall Width 32.3 in

Overall Height 49.8 in

Ground Clearance 13.2 in

Seat Height 37.4 in

Curb Weight 235.8 lb without fuel / 246.0 lb*

Fuel Capacity 1.64 gal

Wheelbase 58.5 in

Color Choices Lime Green

Warranty Not Available



