## <sup>2021</sup> **KX™65**







80/100-12

## POWER

		Front Brakes	Single 180mm disc with single-piston
Engine	2-stroke single, liquid-cooled		caliper
Displacement	64cc	Rear Brakes	Single 180mm disc with single-piston caliper
Bore x Stroke	45.5 x 41.6mm		
Compression Ratio	8.4:1	DETAILS	
Fuel System	24mm Mikuni carburetor	Frame Type	High-tensile steel semi-double cradle
Ignition	CDI with digital advance	Rake/Trail	27°/2.4 in
Transmission	6-speed, return shift, with wet multi-disc	<b>Overall Length</b>	62.6 in
	manual clutch	Overall Width	29.9 in
Final Drive	Chain	Overall Height	37.6 in
PERFORMANCE		Ground Clearance	12.0 in
Front	33mm leading axle telescopic fork with 4-	Seat Height	29.9 in
Suspension / Wheel Travel	way rebound damping/8.3 in	Curb Weight	132.2 lb*
Rear	Uni-Trak® single shock system with 4-way	Fuel Capacity	1.0 gal
Suspension / Wheel Travel	rebound damping and fully adjustable spring preload/9.4 in	Wheelbase	44.1 in

**Rear Tire** 

**Front Tire** 



60/100-14

\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit nicaragua.kawasaki-la.com for full product details.

Lime Green

Not Available

**Color Choices** 

Warranty