MULE[™] 4000







POWER

4-stroke, 2-cylinder, OHV 90° V Liquid-cooled **Engine**

617cc Displacement

Maximum Torque 34.7 lb-ft @ 2500 rpm

Bore x Stroke 2.99x2.68 in

Compression Ratio 10:3:1

Fuel System DFI® with 34mm Mikuni throttle body

Transmission

Final Drive

differential lock

Engine Braking No

(max)

Continuously Variable Transmission (CVT) with (H,N,R)

2WD, shaft. Dual mode rear differential with

Alternator Output 23 amp **Rear Brakes** Drum **Ground Clearance**

Fuel Capacity 6.3 gal

Turning Radius 11.0 ft

Cargo Bed 46.3 x 51.6 x 11.4 in **Dimensions**

7.5 in

(LxWxH)

Cargo Bed Load 800 lb

Capacity

Payload Capacity 1327 lb

Seating Capacity

Towing Capacity 1200 lb

Lighting (2) Halogen headlights (2) tail/brake lights

CAPABILITY

MacPherson Strut/3.9 in Front Suspension / **Wheel Travel**

Rear Suspension / **Wheel Travel**

DeDion Axle/2.8 in

Front Tires

23x11.00-10

Rear Tires Steering

Park Brake Type

Front Brakes

23x11.00-10

Rack-and-pinion

Independent, Mechanical Drum

Drum

DETAILS

Overall Length 116.7 in

Overall Width 62.0 in

Overall Height 75.8 in

Curb Weight 1338.4 lb*

Wheelbase 73.6 in

Instruments Parking brake warning light, coolant temperature

warning light, 12V DC outlet, fuel gauge, hour meter

Color Choices Dark Royal Red

Kawasaki 3-Year Limited Warranty Warranty

Scan with camera to view videos, key features and more.

