MULE 4000 TRANS™









POWER

Engine 4-stroke, 2-cylinder, OHV, 90° V, liquid-cooled

Displacement 617cc

Maximum Torque 34.7 lb-ft @ 2500 rpm

Bore x Stroke 2.99x2.68 in

Compression Ratio 10:3:1

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with (H,N,R)

Final Drive 2WD, shaft. Dual mode rear differential with

differential lock

Engine Braking No

Alternator Output 23 amp

(max)

Ground Clearance

Rear Brakes

Fuel Capacity 6.3 gal

Turning Radius 12.8 ft

Cargo Bed Dimensions 50.4 x 47.6 x 11.2 in (2-person)30.3 x 47.6 x 11.2 in (4-

perso

Drum

7.7 in

Cargo Bed Load

Capacity

(LxWxH)

800 lb (2-person)400 lb (4-person)

Payload Capacity 1330 lb

Seating Capacity 2-4

Towing Capacity 1200 lb

Lighting (2) Halogen headlights (2) tail/brake lights

CAPABILITY

Front Suspension / MacPherson Strut/3.9 in Wheel Travel

Rear Suspension / Wheel Travel

DeDion Axle/2.8 in

Independent, Mechanical Drum

Front Tires

Park Brake Type

23x11.00-10

Rear Tires 23x11.00-10

Steering Electric Power Steering (EPS)

Front Brakes Drum

DETAILS

Overall Length 128.5 in

Overall Width 58.5 in

Overall Height 78.1 in

Curb Weight 1514.1 lb*

Wheelbase 85.2 in

Instruments Parking brake warning light, coolant temperature

warning light, 12V DC outlet, fuel gauge, hour meter

Color Choices Bright White

Warranty Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

