## **MULE 4000 TRANS™**









## **POWER**

**Engine** 4-stroke, 2-cylinder, OHV, 90° V, liquid-cooled

Displacement 617cc

**Maximum Torque** 34.7 lb-ft @ 2500 rpm

**Bore x Stroke** 

**Compression Ratio** 10:3:1

**Fuel System** DFI® with 34mm Mikuni throttle body

**Transmission** Continuously Variable Transmission (CVT) with (H,N,R)

**Final Drive** 

differential lock

**Engine Braking** Nο

23 amp

(max)

2.99x2.68 in

2WD, shaft. Dual mode rear differential with

**Alternator Output** 

## **CAPABILITY**

MacPherson Strut/3.9 in Front Suspension / **Wheel Travel** 

Rear Suspension / **Wheel Travel** 

DeDion Axle/2.8 in

**Front Tires** 23x11.00-10

**Rear Tires** 23x11.00-10

**Steering** Electric Power Steering (EPS) **Park Brake Type** Independent, Mechanical Drum

**Front Brakes** Drum **Rear Brakes** Drum **Ground Clearance** 7.7 in

**Turning Radius** 12.8 ft

6.3 gal

50.4 x 47.6 x 11.2 in (2-person)30.3 x 47.6 x 11.2 in (4-**Cargo Bed Dimensions** (LxWxH)

**Cargo Bed Load Capacity** 

**Fuel Capacity** 

800 lb (2-person)400 lb (4-person)

**Payload Capacity** 1330 lb **Seating Capacity** 2-4

**Towing Capacity** 1200 lb

Lighting (2) Halogen headlights (2) tail/brake lights

## **DETAILS**

**Overall Length** 128.5 in **Overall Width** 58.5 in

**Overall Height** 78.1 in

**Curb Weight** 1514.1 lb\*

Wheelbase 85.2 in

Parking brake warning light, coolant temperature Instruments warning light, 12V DC outlet, fuel gauge, hour meter

**Color Choices Bright White** 

Warrantv Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

