MULE PRO-DXT™ EPS DIESEL FE







POWER

Engine 4-stroke, 3-cylinder, OHV, liquid-cooled, diesel

Displacement 993cc

Maximum Torque 38.3 lb-ft @ 2400 rpm

Bore x Stroke 2.91x3.03 in

Compression Ratio

Fuel System

Transmission

Final Drive

with differential lock

Engine Braking

Alternator Output

(max)

Bosch in-line injection pump

Continuously Variable Transmission (CVT) with (H,L,N,R)

Selectable 2WD/4WD, shaft. Dual mode rear differential

55 amp

CAPABILITY

Front Suspension / Double wishbone/8.7 in **Wheel Travel**

Rear Suspension / **Wheel Travel**

Double wishbone/8.5 (L) /8.7 (R) in

Front Tires 26x9.00-12

Rear Tires 26x11.00-12

Steering Electric Power Steering (EPS), Tilt steering

Park Brake Type Independent, Mechanical Disc

Rear Brakes Dual Disc, 1 piston caliper

Dual Disc, 2 piston caliper

Fuel Capacity 7.9 gal

Turning Radius 16.0 ft

Cargo Bed Dimensions

Ground Clearance

42.7 x 53.7 x 11.0 in (3-person)22.0 x 53.7 x 11.0 in (6-

1000 lb (3-person)350 lb (6-person)

(LxWxH)

Cargo Bed Load

Capacity

10.2 in

Payload Capacity 1581 lb

Seating Capacity 3-person (1 row), 6 person (2 row)

Towing Capacity 2000 lb

Lighting (2) Halogen headlights.

DETAILS

Overall Length 133.3 in

Overall Width 64.0 in

Overall Height 79.5 in

Curb Weight 1964.7 lb*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer,

> fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder

lamps

Color Choices Bright White

Warranty Kawasaki 3-Year Limited Warranty



Front Brakes

