MULE PRO-MX™







| D | N | ١ | A | E | D |
|---|---|---|----|---|---|
| Г | u | ľ | N. | Г | π |

Engine 4-stroke, single cylinder, SOHC, 4-valve liquid-cooled

Displacement 695cc

Maximum Torque 42.7 lb-ft @ 5000 rpm

Bore x Stroke 102.0 x 85.0 mm

Compression Ratio 10.3:1

Fuel System DFI® with 44mm throttle body

Transmission Continuously Variable Transmission (CVT) with

centrifugal clutch, (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output 35.7 amp

(max)

Rear Brakes Dual Disc, 1 piston caliper

Ground Clearance 10.6 in

Fuel Capacity 9.5 gal

Turning Radius 14.0 ft

Cargo Bed

Dimensions (LxWxH)

699 lb (600 lb California models)

33.4 x 44.1 x 9.1 in

Cargo Bed Load Capacity

Payload Capacity

1200 lb

Seating Capacity

Towing Capacity 1500 lb

Lighting (2) Halogen headlights

CAPABILITY

Front Suspension / Double wishbone/8.6 in **Wheel Travel**

Rear Suspension / Double wishbone/9.1 in **Wheel Travel**

Front Tires 25x8.00-12, radial **Rear Tires** 25x10.00-12, radial

Rack & Pinion, Tilt steering **Steering Park Brake Type** Independent, Mechanical Disc

Front Brakes Dual Disc, 2 piston caliper

DETAILS

Overall Length 110.0 in **Overall Width** 60.0 in

Overall Height 74.4 in

1578.8 lb* **Curb Weight**

Wheelbase 78.9 in

Instruments Multi-function display includes digital speedometer,

> fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, neutral, reverse and parking indicators, differential indicator lamp, seatbelt reminder lamps

Color Choices Super Black

Kawasaki 3-Year Limited Warranty Warranty

Scan with camera to view videos, key features and more.

