### 2021

# **MULE SX**™









#### **POWER**

Engine 4-stroke, single-cylinder, OHV, air-cooled

Displacement 401cc

Maximum Torque 20.6 lb-ft @ 2200 rpm

Bore x Stroke 3.23x2.99 in

Compression Ratio 8.3:1

Fuel System Nikki 6C1026 carburetor

Transmission Continuously Variable Transmission (CVT) with (H,N,R)

Final Drive 2WD, shaft. Dual mode rear differential with

differential lock

Engine Braking No

Alternator Output 17 amp

(max)

Rear Brakes Drum

Ground Clearance 6.1 in

Fuel Capacity 4.2 gal

Turning Radius 10.8 ft

Cargo Bed Dimensions

35.6 x 40.9 x 9.6 in

(LxWxH)

Cargo Bed Load

**Capacity** 

400 lb

Payload Capacity 926 lb

Seating Capacity 2

Towing Capacity 1100 lb\*

Lighting (2) Halogen headlights, tail/brake lights

## **CAPABILITY**

Front Suspension / MacPherson Strut/3.1 in Wheel Travel

Rear Suspension /

Unit Swingarm/3.1 in

Wheel Travel

22x9.00-10

Front Tires
Rear Tires

22x11.00-10

Steering

Rack-and-pinion, Tilt steering

**Park Brake Type** 

Independent, Mechanical Drum

Front Brakes

Drum

#### **DETAILS**

**Overall Width** 

Overall Length 106.7 in

Overall Height 70.1 in

Curb Weight 967.6 lb\*\*

Wheelbase 70.1 in

Instruments

Fuel gauge, hour meter, oil temp light, parking brake

light

52.6 in

**Color Choices** 

Timberline Green, Dark Royal Red

Warranty

Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features and more.



\*Requires Optional Hitch