

2021

NINJA® 1000SX

Kawasaki
Let the Good Times Roll®



METALLIC CARBON GRAY/METALLIC DIABLO BLACK



POWER

Engine	4-stroke, In-Line Four, DOHC, 16-valve, liquid-cooled
Displacement	1,043cc
Bore x Stroke	77.0 x 56.0mm
Compression Ratio	11.8:1
Fuel System	DFI® w/38mm Keihin throttle bodies (4) and oval sub-throttles
Ignition	TCBI with digital advance
Transmission	6-speed, return shift
Final Drive	Sealed Chain
Electronic Rider Aids	Kawasaki Traction Control (KTRC), Kawasaki Intelligent anti-lock Brake System (KIBS), Power Mode, Kawasaki Corner Management Function (KCMF), Kawasaki Quick Shifter (KQS) (Up-Down)

Rear Suspension / Wheel Travel	Horizontal back-link with stepless rebound damping, remotely adjustable spring preload/5.7 in
Front Tire	120/70 ZR17
Rear Tire	190/50 ZR17
Front Brakes	Dual 300mm semi floating discs with radial mounted, monobloc opposed 4-piston calipers, ABS
Rear Brakes	Single 250mm disc, ABS

PERFORMANCE

Front Suspension / Wheel Travel	41mm inverted cartridge fork with stepless compression and rebound damping, adjustable spring preload/4.7 in
---------------------------------	--

DETAILS

Frame Type	Aluminum backbone
Rake/Trail	24.0° / 3.9 in
Overall Length	82.7 in
Overall Width	32.5 in
Overall Height	46.9 / 48.2 in
Ground Clearance	5.3 in
Seat Height	32.3 in
Curb Weight	513.8 lb*
Fuel Capacity	5.0 gal
Wheelbase	56.7 in
Color Choices	Metallic Carbon Gray / Metallic Diablo Black
Warranty	12 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit nicaragua.kawasaki-la.com for full product details.