
# NINJA® ZX™-14R ABS









#### **POWER**

**Engine** 4-stroke, In-Line Four, DOHC, 16-valve,

liquid-cooled

**Displacement** 1,441cc

**Bore x Stroke** 84.0 x 65.0mm

Compression

**Ratio** 

**Fuel System** DFI® w/44mm Mikuni throttle bodies (4)

**Ignition** TCBI, battery powered & electronic advance

**Transmission** 6-speed return shift

**Final Drive** Sealed chain

**Electronic Rider** Kawasaki Traction Control (KTRC), Power

Mode, ABS

# 12.3:1

**Aids** 

### **PERFORMANCE**

Front 43mm inverted cartridge fork with adjustable Suspension / preload, 18-way compression and 15-way **Wheel Travel** rebound damping adjustment/4.6 in

Rear Suspension / **Wheel Travel** 

Bottom-link Uni-Trak® and gas-charged shock with adjustable preload, stepless rebound and compression damping adjustments, adjustable ride height/4.9 in

**Front Tire** 120/70ZR17 **Rear Tire** 190/50ZR17

**Front Brakes** Dual semi-floating 310mm discs with

Brembo® 4-piston M50 monobloc calipers

and ABS

Single 250mm petal disc with twin-piston **Rear Brakes** 

caliper and ABS

## **DETAILS**

Aluminum monocoque **Frame Type** 

Rake/Trail 23.0°/3.7 in

**Overall Length** 85.4 in

**Overall Width** 30.3 in

**Overall Height** 46.1 in

4.9 in Ground

Clearance

**Seat Height** 31.5 in

**Curb Weight** 593.1 lb\*

**Fuel Capacity** 5.8 gal

Wheelbase 58.3 in

**Color Choices** Pearl Storm Gray / Metallic Diablo Black

Warranty 12 Month Limited Warranty



