NEW 2021

TERYX KRX® 1000 eS









POWER

Ignition

Engine 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled

Displacement 999cc

76.7 lb-ft @ 7000 rpm **Maximum Torque**

Bore x Stroke 92.0 x 75.1 mm

Compression Ratio 11.5:1

Fuel System DEL with two 50mm throttle hodies

Starting System Electric

Automatic CVT with centrifugal clutch (H,L,N,R) **Transmission**

Final Drive Selectable 2WD/4WD with locking front differential, shaft

TCBI with electronic advance

Engine Braking

CAPABILITY

Front Suspension / Wheel Travel

Double wishbone, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/18.6 in.

Rear Suspension / Wheel Travel

4-link trailing-arm rear suspension, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/21.1 in.

Front Tires MAXXIS Carnivore 31 x 10.00R15 8PR

Rear Tires MAXXIS Carnivore 31 x 10.00R15 8PR

Steering Electric Power Steering (EPS) / rack-and-pinion

Front Brakes Dual hydraulic discs with two-piston calipers

14.0 in / 14.4 in

Rear Brakes Dual hydraulic discs with single-piston calipers

Standard Ground Clearance/Maximum

Ground Clearancet

Fuel Capacity 10.6 gal **Turning Radius** 20.3 ft

Cargo Bed Dimensions 14.6 x 33.1 x 9.1 in (LxWxH)

Cargo Bed Load

Capacity

Payload Capacity 781 lbs

351 lbs

Seating Capacity 2

Towing Capacity N/A

(2) LED headlights, (2) LED taillights, LED stoplight Lighting

DETAILS

Frame Ladder type, tubular steel

Overall Length 132.1 in Overall Width 68.1 in **Overall Height** 77.0 in

1944.8 lbs (1947.0 CA)* **Curb Weight**

Wheelbase 98.8 in

Instruments

screen that offers three selectable display modes (Digital, Analogue, Simple) and can auto adjust screen brightness to suit available light. Display functions include speedometer, tachometer, fuel gauge, gear indicator (L, H, N, R), driving mode (2WD/4WD/4WD+Diff Lock), power mode (Full/Low), suspension mode (Soft/Normal/Firm), clock, CVT temperature, digital tachometer, odometer, dual trip meters, total time, trip time, average speed, water temperature, battery voltage, Bluetooth indicator, telephone call indicator, main indicator, economical riding indicator, maintenance reminder, neutral indicator, reverse indicator, headlight high-beam indicator, battery warning lamp, EPS warning lamp, CVT belt warning lamp, seatbelt warning lamp, parking indicator lamp, oil warning lamp, water temperature warning lamp, engine check lamp.

Multi-function digital meter with high-grade full-color TFT LCD

Color Choices Metallic Onyx Black

6 months Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2025 Kawasaki Motors Corp., U.S.A.