







## **POWER**

Engine 4-stroke, 4-cylinder, DOHC, 4-valve, liquid-cooled,

supercharged

Displacement 998cc

Bore x Stroke 76.0 x 55.0mm

Compression

Ratio

11.2:1

Maximum Torque 101.0 lb-ft

Fuel System DFI, 40mm Throttle Bodies

Ignition TCBI w/ Digital Advance

**Transmission** 6-speed dog-ring, return shift

Final Drive Sealed chain

**Electronic Rider** 

Aids

Integrated Riding Modes, Kawasaki Cornering Management Function (KCMF), Power Modes (3), Kawasaki Launch Control Mode (KLCM), Kawasaki Traction Control (KTRC), Kawasaki Launch Control Mode (KLCM), Kawasaki Engine Brake Control (KEBC), Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Quick Shifter (KQS) (upshift & downshift), Electronic Cruise Control

## **PERFORMANCE**

Front Suspension / Wheel Travel

Showa SFF-BP Fork with Adjustable Compression and Rebound Damping, 20 Turns Spring Preload

Adjustability / 4.7 in

Rear Suspension / Wheel Travel

Uni-Trak®, Showa Shock with Adjustable Rebound Damping / 5.3 in

Front Tire 120/70-17

**Rear Tire** 190/55-17

Front Brakes Dual 320mm Disc w/Radial-mount Brembo M4.32

Calipers, KIBS

**Rear Brakes** Single 250mm disc with single-piston caliper, KIBS

## **DETAILS**

Frame Type Trellis, high tensile steel

Rake/Trail 24.9°/4.1in

Overall Length 82.1 in

Overall Width 31.9 in

Overall Height 44.5 in

**Ground Clearance** 5.5 in

Seat Height 32.7 in

Curb Weight 527.0 lb\*

Fuel Capacity 5.0 gal

Wheelbase 57.3 in

Special Features Rideology the App Smartphone Connectivity, TFT

Instrumentation

Color Choices Metallic Diablo Black / Metallic Flat Spark Black

**Warranty** 12 Month Limited Warranty



