2024 KLX®230R








100/100-18

POWER

			Front Brakes	Single 240mm petal disc with a dual-
	Engine	4-stroke single, SOHC, air-cooled		piston caliper
	Displacement	233cc	Rear Brakes	Single 220mm petal disc with single- piston caliper
	Bore x Stroke	67.0 x 66.0mm		
	Compression Ratio	9.4:1	DETAILS	
	Fuel System	DFI® with 32mm Keihin throttle body	Frame Type	High-tensile steel, box-section perimeter
	Ignition	TCBI Electronic Advance	Rake/Trail	26.5°/4.4 in
	Transmission	6-speed, return shift with wet multi-disc	Overall Length	80.5 in
	1141151111551011	manual clutch	Overall Width	33.1 in
	Final Drive	Chain	Overall Height	47.2 in
PERFORMANCE			Ground Clearance	11.8 in
	Front	37mm telescopic fork/9.8 in	Seat Height	36.4 in
	Suspension / Wheel Travel		Curb Weight	253.6 lb* / 262.3 lb* CA Model
	Rear	Uni-Trak [®] linkage system and single shock	Fuel Capacity	1.7 gal
	Suspension / Wheel Travel	with adjustable spring preload/9.9 in	Wheelbase	53.5 in

Rear Tire

Front Tire



to view videos, key features and more.



80/100-21

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit nicaragua.kawasaki-la.com for full product details.

Lime Green, Battle Gray

6 Month Limited Warranty

Color Choices

Warranty