## KLX®300R









## **POWER**

Engine 4-stroke single, DOHC, liquid-cooled

Displacement 292cc

Bore x Stroke 78.0 x 61.2mm

Compression

Ratio

Fuel System DFI® with 34mm Keihin throttle body

11.1:1

Ignition TCBI Electronic Advance

**Transmission** 6-speed, return shift with wet multi-disc

manual clutch

Final Drive Chain

**Front Brakes** 

**Rear Tire** 

Single 270mm petal disc with a dual-

piston caliper

4.6 x 18

**Rear Brakes** Single 240mm petal disc with single-

piston caliper

## **PERFORMANCE**

Front
Suspension /
Wheel Travel
43mm inverted telescopic fork with
adjustable compression damping /11.2 in

Rear Suspension / Wheel Travel Uni-Trak® gas charged shock with piggyback reservoir with adjustable compression, rebound damping and

spring preload/11.2 in

Front Tire 3.0 x 21

## **DETAILS**

Frame Type Semi-Double Cradle

Rake/Trail 26.9°/4.3 in

Overall Length 86.6 in

Overall Width 32.5 in

Overall Height 49.0 in

Clearance

Ground

Seat Height 35.4 in

**Curb Weight** 282.2 lb\* / 286.7 lb\* CA Model

11.8 in

Fuel Capacity 2.1 gal

Wheelbase 56.5 in

**Color Choices** Lime Green, Battle Gray

**Warranty** 6 Month Limited Warranty



