

2024

KLX[®]300R



- LIME GREEN
- BATTLE GRAY



| POWER | | Rear Tire | 4.6 x 18 |
|---------------------------------|--|------------------|--|
| Engine | 4-stroke single, DOHC, liquid-cooled | Front Brakes | Single 270mm petal disc with a dual-piston caliper |
| Displacement | 292cc | Rear Brakes | Single 240mm petal disc with single-piston caliper |
| Bore x Stroke | 78.0 x 61.2mm | DETAILS | |
| Compression Ratio | 11.1:1 | Frame Type | Semi-Double Cradle |
| Fuel System | DFI [®] with 34mm Keihin throttle body | Rake/Trail | 26.9° / 4.3 in |
| Ignition | TCBI Electronic Advance | Overall Length | 86.6 in |
| Transmission | 6-speed, return shift with wet multi-disc manual clutch | Overall Width | 32.5 in |
| Final Drive | Chain | Overall Height | 49.0 in |
| PERFORMANCE | | Ground Clearance | 11.8 in |
| Front Suspension / Wheel Travel | 43mm inverted telescopic fork with adjustable compression damping / 11.2 in | Seat Height | 35.4 in |
| Rear Suspension / Wheel Travel | Uni-Trak [®] gas charged shock with piggyback reservoir with adjustable compression, rebound damping and spring preload / 11.2 in | Curb Weight | 282.2 lb* / 286.7 lb* CA Model |
| Front Tire | 3.0 x 21 | Fuel Capacity | 2.1 gal |
| | | Wheelbase | 56.5 in |
| | | Color Choices | Lime Green, Battle Gray |
| | | Warranty | 6 Month Limited Warranty |

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit nicaragua.kawasaki-la.com for full product details.