KX[™]450X







POWE	ŁΚ
------	----

Engine 4-stroke single, DOHC, liquid-cooled

Displacement 449cc

96.0 x 62.1mm

Bore x Stroke
Compression

12.5:1

Fuel System

DFI® with 44mm Keihin throttle body

Ignition

Ratio

Digital CDI with handlebar-controlled Power

Modes

Transmission

5-speed, return shift, with wet multi-disc manual

clutch and hydraulic clutch actuation

Final Drive

Chain

Electronic Rider Aids Power Modes, Kawasaki TRaction Control (KTRC),

Launch Control Mode

PERFORMANCE

Front Suspension / Wheel Travel

49mm inverted telescopic coil-spring fork with 21way adjustable compression and 22-way adjustable rebound damping/12.0 in

Rear Suspension / Wheel Travel

Uni-Trak® gas charged shock with piggyback reservoir with adjustable dual-range compression damping (19-way low speed and 4.25 turn stepless high speed), 23-way adjustable rebound damping and stepless adjustable preload/12.1 in

Front Tire 80/100-21

Rear Tire 120/80-18

Front Brakes Single semi-floating 270mm Braking/Sunstar

petal disc with Brembo master cylinder and dual-

piston caliper

Rear Brakes Single 240mm Braking/Sunstar petal disc with

single-piston caliper

DETAILS

Frame Type Aluminum perimeter

Rake/Trail 27.0°/4.6 in

Overall Length 85.6 in

Overall Width 32.1 in

Overall Height 49.6 in

Ground Clearance 13.2 in

Seat Height 37.4 in

Curb Weight 239.8 lb* without fuel / 249.9 lb*

Fuel Capacity 1.64 gal

Wheelbase 58.3 in

Special Features | Smartphone Connectivity via RIDEOLOGY THE APP

Color Choices Lime Green

Warranty Not Available



