

# 2024 KX™ 85

**Kawasaki**  
Let the Good Times Roll®



 LIME GREEN



## POWER

<b>Engine</b>	2-stroke single with exhaust power valve (KIPS), liquid-cooled
<b>Displacement</b>	84cc
<b>Bore x Stroke</b>	48.5 x 45.8mm
<b>Compression Ratio</b>	10.9:1 (low speed) / 9.0:1 (high speed)
<b>Fuel System</b>	28mm Keihin carburetor
<b>Ignition</b>	CDI with Digital Advance
<b>Transmission</b>	6-speed, return shift, with wet multi-disc manual clutch
<b>Final Drive</b>	Chain

<b>Rear Tire</b>	90/100-14
<b>Front Brakes</b>	Single 220mm petal disc with dual-piston caliper
<b>Rear Brakes</b>	Single 184mm petal disc with single-piston caliper

## PERFORMANCE

<b>Front Suspension / Wheel Travel</b>	36mm inverted telescopic cartridge fork with 20-way compression damping/10.8 in
<b>Rear Suspension / Wheel Travel</b>	Uni-Trak® single shock system with 24-way compression and 21-way rebound damping, plus adjustable spring preload/10.8 in
<b>Front Tire</b>	70/100-17

## DETAILS

<b>Frame Type</b>	High-tensile steel perimeter design with subframe member
<b>Rake/Trail</b>	29° / 3.8 in
<b>Overall Length</b>	72.0 in
<b>Overall Width</b>	30.1 in
<b>Overall Height</b>	43.3 in
<b>Ground Clearance</b>	11.4 in
<b>Seat Height</b>	32.7 in
<b>Curb Weight</b>	164.4 lb*
<b>Fuel Capacity</b>	1.32 gal
<b>Wheelbase</b>	49.8 in
<b>Color Choices</b>	Lime Green
<b>Warranty</b>	Not Available

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [nicaragua.kawasaki-la.com](http://nicaragua.kawasaki-la.com) for full product details.