
MULE PRO-FXT™ 1000 LE









POWER

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled, gas

Displacement 999cc

Maximum Torque 61.5 lb-ft

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 10.1:1

Fuel System DFI® with 38mm throttle body

Transmission Continuously Variable Transmission (CVT) with (L,H,N,R)

Final Drive Selectable 2WD/4WD, shaft Dual mode rear differential

with differential lock

Engine Braking

Alternator Output

(max)

90 amp

CAPABILITY

Double wishbone/11.0 in Front Suspension / **Wheel Travel**

Rear Suspension / **Wheel Travel**

Double wishbone/10.1 in

Front Tires

26 x 9.00-12, radial

Rear Tires

26 x 11.00-12, radial

Steering

Electric Power Steering (EPS), Tilt steering

Park Brake Type

Independent, Mechanical Disc

Front Brakes

Dual Disc, 2 piston caliper

Rear Brakes

Dual Disc, 1 piston caliper

Ground Clearance 12.6 in (max), 11.6 in (std)

Fuel Capacity

Turning Radius Cargo Bed

Dimensions (LxWxH)

Cargo Bed Load

Capacity

Payload Capacity

Seating Capacity

Towing Capacity

Lighting

7.9 gal

16.0 ft

42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-

999 lb (3-person) / 350 lb (6-person) / 348 lb CA Model

person)

1,616.3 lb / 1,263.5 lb CA Model

3-person (1 row), 6 person (2 row)

2,000 lb

(2) Halogen headlights. (2) LED headlights

DETAILS

Overall Length 135.8 in

Overall Width 64.0 in

Overall Height 80.9 in

Curb Weight 1,913.9 lb* / 1,916.1 lb* CA Model

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer,

fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt

reminder lamps

Additional Features Roof, Additional Front Cup Holders

Color Choices

Metallic Onyx Black, Metallic Sierra Blue

Warranty

Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

