NINJA H2® ABS









120/70 ZR17 (58W)

200/55 ZR17 (78W)

POWER

Engine Liquid-cooled, 4-stroke, In-Line Four, DOHC, 16-

valve

8 5.1

Displacement 998cc

Bore x Stroke 76.0 x 55.0mm

Compression

Ratio

Maximum Torque 104.9 lb-ft @ 11,000 rpm

DFI® with 50mm throttle bodies (4) with dual **Fuel System**

injection; Kawasaki Supercharger

Ignition Digital

Transmission 6-speed, return, dog-ring

Final Drive Sealed chain

Electronic Rider

Aids

Kawasaki Cornering Management Function (KCMF), Kawasaki TRaction Control (KTRC), Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Engine Brake Control (KEBC), Kawasaki Quick Shifter (KQS) (upshift & downshift), Öhlins Electronic Steering Damper

DETAILS

Overall Height

Seat Height

Warranty

Front Tire

Rear Tire

Front Brakes

Rear Brakes

Trellis, high-tensile steel, with swingarm mounting **Frame Type**

Dual radial-mount, opposed 4-piston Brembo

Opposed 2-piston calipers, single 250mm disc,

Stylema® calipers, dual semi-floating 330mm discs, Kawasaki Intelligent anti-lock Brake System (KIBS)

Kawasaki Intelligent anti-lock Brake System (KIBS)

plate

44.3 in

32.5 in

524.8 lb*

24.5° / 4.1 in Rake/Trail

Overall Length 82.1 in

Overall Width 30.3 in

Ground Clearance 5.1 in

Curb Weight

Fuel Capacity 4.5 gal

Wheelbase 57.3 in

Special Features Smartphone Connectivity via RIDEOLOGY THE APP,

all-LED lighting, Highly Durable Paint, TFT

Instrumentation

Color Choices Mirror Coated Spark Black

12 Month Limited Warranty

PERFORMANCE

Front Suspension / Wheel Travel

43mm inverted fork with adjustable rebound and compression damping, spring preload adjustability and top-out springs/4.7 in

Rear Suspension / Wheel Travel

Uni-Trak®, Öhlins TTX36 gas charged shock with piggyback reservoir, 24-way compression and rebound damping adjustability, 15-way spring preload adjustability, and top-out spring/5.3 in

Scan with camera to view videos. key features and more.

