NINJA® ZX™-14R 40th ANNIVERSARY EDITION ABS









D	N		M	Г	D
r	u	ľ	N	г	ĸ

Engine 4-stroke, In-Line Four, DOHC, 16-valve,

liquid-cooled

Displacement 1,441cc

Bore x Stroke 84.0 x 65.0mm

Compression

Ratio

12.3:1

Fuel System DFI® with 44mm Mikuni throttle bodies (4)

Ignition TCBI, battery powered & Electronic Advance

Transmission 6-speed, return shift

Final Drive Sealed chain

Electronic Rider Kawasaki TRaction Control (KTRC), Power Modes, Anti-lock Brake System (ABS)

Aids

PERFORMANCE

Front 43mm inverted cartridge fork with adjustable Suspension / preload, 18-way compression and 15-way **Wheel Travel** rebound damping adjustment/4.6 in

Rear Suspension / **Wheel Travel** Bottom-link Uni-Trak® and gas-charged shock with adjustable preload, stepless rebound and compression damping adjustments, adjustable ride height/4.9 in

Front Tire 120/70ZR17 **Rear Tire** 190/50ZR17

Front Brakes Dual semi-floating 310mm Brembo discs with

dual radial-mounted Brembo 4-piston M50

monobloc calipers and ABS

Single 250mm disc with twin-piston caliper **Rear Brakes**

and ABS

DETAILS

Aluminum monocoque **Frame Type**

Rake/Trail 23.0°/3.7 in

Overall Length 85.4 in

Overall Width 30.3 in

Overall Height 46.1 in

4.9 in Ground Clearance

31.5 in **Seat Height**

593.1 lb* **Curb Weight**

Fuel Capacity 5.8 gal

Wheelbase 58.3 in

Color Choices Lime Green/Pearl Crystal White/Blue

Warranty 12 Month Limited Warranty

Scan with camera to view videos. key features and more.

