VERSYS®-X 300 ABS









POWER

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled

Displacement 296cc

Bore x Stroke 62.0 x 49.0mm

Compression

Ratio

10.6:1

Maximum Torque 19.2 lb-ft

. . . .

DFI® with 32mm throttle bodies (2)

Fuel System
Ignition

TCBI with Digital Advance

Transmission

6-speed, return shift

Final Drive

Sealed chain

Electronic Rider

Anti-lock Brake System (ABS), Economical

Δids

Riding Indicator

PERFORMANCE

Front
Suspension /
Wheel Travel

Telescopic fork/5.1 in

Rear Suspension / Wheel Travel Uni-Trak® swingarm with 5-way spring

preload adjustment/5.8 in

Front Tire 100/90-19M/C 57S

Rear Tire 130/80-17M/C 65S

Front Brakes Single 290mm disc, ABS

Rear Brakes Single 220mm disc, ABS

DETAILS

Frame Type Tubular, diamond

Rake/Trail 24.3°/4.3 in

Overall Length 85.4 in

Overall Width 33.9 in

Overall Height 54.7 in

Ground 7.1 in Clearance

Seat Height 32.1 in

Curb Weight 385.9 lb*

Fuel Capacity 4.5 gal

Wheelbase 57.1 in

Color Choices Pearl Matte Sage Green/Metallic Matte

Carbon Gray

Warranty 12 Month Limited Warranty



